



ORLEN OIL MIXOL S

General features

Oil manufactured from highly refined base oils and a set of enriching additives.

It guarantees:

- very good mixing with fuel,
- good cleaning and dispersing properties which limit formation of carbon deposit, ash slurry, lake and sediments,
- low flow temperature which allows application in difficult operating conditions, very good anticorrosive properties.

Application

ORLEN OIL Mixol S is intended for two-stroke engines with spark ignition lubricated in a mixture. It includes dissolvent providing easy mixing with fuel. It may be directly poured into the fuel tank. The most favourable oil and fuel ratio is defined by the engine operating manual.

Dosage: 2% of the fuel volume /1:50/ unless otherwise recommended by the engine manufacturer.

Quality class

API : TB/TA

Standards, approvals, specifications

Meets requirements:

PN-70/C-96092

Physical and chemical properties

| Parameters | Unit | Typical values |
|--|--------------------|----------------|
| Kinematic viscosity 100 ^o C | mm ² /s | 6.0 |
| Flow temperature | ^o C | -40 |
| Ignition temperature | ^o C | 85 |
| Sulphate ash | % | 0.11 |

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

v.2 /2024.03.11