



ORLEN OIL PETRYGO HEAVY

General features:

New generation, long-life radiator fluid – ORLEN OIL PETRYGO HEAVY ANTIFREEZE is intended for use in the cooling systems of trucks, buses, agricultural machinery and heavy construction equipment. The fluid forms a thin protective film in the system, providing corrosion and cavitation protection for the cooling system components for up to 150,000 km or 5 years. The fluid is frost resistant up to -37°C and provides excellent protection against engine overheating.

- model heat exchange parameters
- excellent protection of the cooling system against corrosion and cavitation
- safe for rubber and plastic elements
- guaranteed crystallization temperature -37°C
- protects the system against overheating
- prevents deposits and limescale
- safe for the environment

Application:

For cooling the diesel engines of vans, trucks, buses and heavy machinery. Appropriate for engines equipped with aluminium, cast-iron and mixed radiator systems. Ready-to-use fluid. Follow the manual supplied by the car manufacturer.

Any loss is recommended to be replenished with the PETRYGO HEAVY ANTIFREEZE fluid.

Shelf life: 5 years in case of storage in a sealed container + 5 years of use in the cooling system.

Standards, specifications:

Approvals:

MAN 324 type Si-OAT

Daimler Truck Fluid Release 29D120 (MB 326.5)

Meets requirements:

VW/Audi/Seat/Skoda TL 774-G (G12++)

Cummins CES 14603

DEUTZ DQC CC-14

PN-C 40007:2000

ASTM D3306

ASTM D4985

BS 6580

ÖNORM V 5123

SAE J1034

Manufactured according to the PN-EN ISO 9001:2015 quality management system.

Packaging:

20L, 205L



Physical and chemical properties

Parametrs	Units	Typical values
Colour	[-]	pink
Density at 20°C	[g/ml]	1,064
Boiling point	[°C]	110
pH	[-]	7,5
Crystallization temperature	[°C]	-37

The above physico-chemical specifications are typical values. Actual values are described on quality certificates for each product batch.

Version

1 / 2024-03-19