



ORLEN OIL PETRYGO PLUS G12+

DESCRIPTION:

New generation long-life radiator fluid – Orlen Oil Petrygo PLUS G12+. Based on the OAT Organic Acid Technology. Contains active corrosion inhibitors microparticles, providing continuous operation without sticking to the internal surfaces of the cooling system. The fluid prevents the occurrence of corrosion centres and cavitation for up to 5 years or 250,000 km. The fluid is frost resistant up to -37°C and provides excellent protection against engine overheating.

Does not contain toxic nitrites, silicates, amines or phosphates.

- model heat exchange parameters
- excellent protection of the cooling system against corrosion and cavitation
- safe for rubber and plastic elements
- guaranteed crystallization temperature -37°C
- protects the system against overheating
- prevents deposits and limescale
- safe for the environment.

APPLICATIONS:

For cooling all types of engines in passenger cars and trucks equipped with aluminium, cast-iron and mixed radiator systems. Miscible with all G12 and G11 standard cooling fluids.

Ready-to-use fluid. Follow the manual supplied by the car manufacturer. Any loss is recommended to be replenished with the Orlen Oil Petrygo PLUS fluid.

Shelf life: 5 years in case of storage in a sealed container + 5 years of use in the cooling system.

STANDARDS, APPROVALS, SPECIFICATIONS:

Approvals:

MAN 324 type SNF

Daimler Truck Fluid Release 29D110 (MB 326.3)

Volkswagen TL 774 F

DAF Specification 74002

Meet requirements:

MB-Approval 326.3

GM 6277M

Ford specification WSS-M97B44-D

PN-C 40007:2000

ASTM D3306

ASTM D4656

ASTM D6210

BS 6580



Manufactured according to the PN-EN ISO 9001:2015 quality management system.

Packaging:

1L, 2L, 5L, 20L, 205L

Physical and chemical properties:

Parameters	Unit	Typical value
Color	[-]	pink
Density at 20°C	[g/ml]	1,071
Boiling point	[°C]	109
pH	[-]	8
Crystallisation temperature	[°C]	-37

Note: The above physico-chemical specifications are typical values. Actual values are described on quality certificates for each product batch.