



ORLEN OIL GEAR LS GL-5 85W-140

General features:

High quality, mineral, multigrade oil for manual transmissions. Designed for the lubrication of manual gearboxes and limited slip gears, so called LS.

It guarantees:

- good corrosion and anti-rust protection
- high loading transfer capacity
- very good antifoaming parameters
- perfect purity of transmission

Application:

ORLEN OIL Gear LS 85W-140 designed for year round use in manual transmission for cars, trucks and buses operating in difficult conditions. Especially recommended for differentials with Limited Slip – LS. Recommended for the lubrication of the front axles of tractors, harvesters and main gears and rare axles of other mechanical/motor devices for which the manufacturer recommends the use of API GL-5 gear oil.

Viscosity grade:

SAE: 85W-140

Quality class:

API: GL-5

Standards, Approvals, specification:

ZF TE-ML 16E

Physical and chemical properties:

Parameters	Unit	Typical value
Viscosity grade SAE	-	85W-140
Kinematic viscosity at 100°C	mm ² /s	24,93
Viscosity index	-	92
Pour point	°C	- 18
Low temperature viscosity, at -12°C	cP	61 390

ATTENTION: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot

v1 / 2024-04-30