



ORLEN OIL CLASSIC DIESEL MINERAL 15W-40

General features

High quality, mineral motor oil, designed for year-round operation dedicated to self-ignition engines. Exceptional quality of the mineral base used, and very good antioxidant properties, ensure superb engine protection and reduced oil consumption. Excellently prevents deposits formation.

It guarantees:

- Perfect deposit control,
- High engine cleanliness,
- Excellent heat abstraction from the system,
- increases engine power by reducing friction
- Very good engine leakproofness.

Application

ORLEN OIL Classic Diesel Mineral 15W-40 – designed especially for vehicles powered by Diesel engines. Recommended both for cars and light trucks with and without turbochargers. The oil proves itself in year-long driving conditions, not only on the motorways, but also in regular urban traffic conditions.

Quality class

API: CF

Viscosity grad

SAE: 15W-40

Standards, approvals, specifications

Meets the requirements of:
Mercedes – Benz 229.1

Physical and chemical properties

Parameters	Unit	Typical values
Viscosity class SAE	-	15W-40
Kinematic viscosity in temp. 100 °C	mm ² /s	14,1
Viscosity index	-	142
Pour point	°C	-33
Flash point	°C	235
Total Basic Number (TBN)	mg KOH/g	8,7
Noack evaporative loss	% (m/m)	10,5

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

v. 2 /2024.03.07