



ORLEN OIL PETRYGO EVO

General features:

A new formula of ORLEN OIL PETRYGO EVO is the latest generation of coolants recommended for use in cars with Internal Combustion Engines, Hybrids and Electric Cars with an indirect battery cooling system (BEV). It is produced on the basis of highquality ethylene glycol and an innovative additive package based on salts of organic acids and inorganic compounds. Miscible with all VW Group standard fluids, including: VW G11, G12, G12+, G12++, G13. The fluid protects against corrosion and cavitation.

ORLEN OIL PETRYGO EVO is resistant to freezing down to -37°C and provides excellent protection against overheating

Application:

Ready-to-use coolant. Use in accordance with the instruction manual recommended by the car manufacturer. Exclusive use of PETRYGO EVO is recommended. Shelf life counted from the production date shown on the packaging: 3 years when stored in a tightly closed container + 5 years in the cooling system.

Standards, specifications:

Meets requirements:
VW TL 774-L (G 12 EVO),
ASTM D3306,
PN-C-40007,
JIS K2234,
FVV R 530,
BS 6580,
AFNOR NF-R-15-601

Manufactured according to the PN-EN ISO 9001:2015 quality management system.

Physical and chemical properties

Parameters	Units	Typical values
Colour	[-]	pink
Density at 20°C	[g/ml]	1,071
Boiling point	[$^{\circ}\text{C}$]	109
pH	[-]	8
Crystallization temperature	[$^{\circ}\text{C}$]	-37

The above physico-chemical specifications are typical values. Actual values are described on quality certificates for each product batch.

Version

1 / 2024-03-19