



## ORLEN OIL DIESEL FLEET 10W-40

### General features

Mainly compatible with engines that meet EURO 3 emission and earlier standards. It ensures a high level of driving culture of the power unit by preventing the formation of deposits and carbon deposits as well as the wear of lubricated elements. Conventional SAPS level - no possibility of use in vehicles equipped with exhaust after treatment systems in the form of particulate filters

### Application

High-quality all-season SHPD type engine oil. Recommended for use in high-speed, four-stroke diesel engines, also those operated in harsh conditions, tractor units, trucks, vans and special cars adapted to meet the EURO III and earlier emission standards. Recommended for standard exchange intervals.

### Quality class

API: API CI-4/CH-4/CG-4/CF-4/SL

### Viscosity grad

SAE: 10W-40

### Physical and chemical parameters:

Parameters	Unit	Typical values
SAE viscosity grade	-	10W-40
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	14,0-16,3
Viscosity index	-	145
Flow temperature	°C	-36
Ignitron temperature	°C	210
Base number, no lower than	mgKOH/g	10

**Note:** Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

Version 1 / 2024-06-04