



## ORLEN OIL AGRO STOU 10W-30

### General characteristics:

ORLEN OIL Agro STOU 10W-30 is a high quality, multi-purpose (gear, motor, hydraulic) mineral oil. The unique and modern composition of specially selected mineral bases and additives meets the construction requirements of modern agricultural equipment manufacturers.

The oil guarantees:

- excellent lubricating and anti-wear properties,
- good compatibility with seals,
- system vibration damping,
- high resistance to oxidation,
- compatibility with a variety of sealing materials.

### Application:

ORLEN OIL Agro STOU 10W-30 is recommended for lubrication of motors, hydraulic systems and manual transmissions in various types of agricultural machinery from different manufacturers. It is suitable for use in wet brake systems.

### Viscosity class:

SAE: 10W-30

### Quality class:

API: CG-4, GL-4

ACEA: E3

### Standards, Approvals, Specifications:

#### Meets requirements:

Massey Ferguson M1145,  
Massey Ferguson M1144,  
Massey Ferguson M1139  
Ford M2C 159B,  
Ford M2C 159C,  
John Deere JDM J27,  
New Holland 82009201,  
New Holland 82009202,  
New Holland 82009203  
ZF TE –ML 06A ,  
ZF TE –ML 06B,  
ZF TE –ML 06C,  
ZF TE –ML 07B  
CCMC D4,  
Sperry Vickers/Eaton: M2950S,  
Sperry Vickers/Eaton: I-286-S,  
Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid,  
AFNOR NFE68603E .



**Physicochemical parameters:**

Parameters	Units	Typical values
SAE viscosity class	-	10W-30
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	9.98
viscosity index	-	135
pour point	0C	-30
TBN	mg KOH/g	10.0

Note: The foregoing values of physical and chemical parameters are typical values. Actual values are specified in the quality certificates attached to each product batch.

v1 / 2024-02-27