



ORLEN OIL ULTOR DIESEL 15W-50

General features

Mineral engine oil designed for lubrication of heavy-loaded compression-ignition high-power engines with or without turbochargers. It is particularly recommended for standard drain intervals in engines of trucks, cars, farm tractors, buses as well as other high-performance vehicles, if the manufacturer allows the use of this quality and viscosity grade oil. 15W-50 grade provide superior protection at high engine temperatures.

Application

ULTOR DIESEL 15W-50 is intended for all types of naturally aspirated and turbo-charged diesel engines. With its unique formulation of enriching additives, it can be used in trucks, buses and construction machinery operated in extreme conditions. It is suitable for use in engines meeting the Euro II standard.

Quality class

API: CG-4/CF-4/CF

Viscosity grad

SAE: 15W-50

Standards, approvals, specifications

Meets requirements:

Mercedes-Benz 228.1
MAN 271

Physical and chemical properties

Parameters	Unit	Typical values
SAE viscosity grade	-	15W-50
Kinematic viscosity at 100 °C	mm ² /s	17,5-19,5
Viscosity index	-	130
Flow temperature	°C	-27
Sulphide ash	%	1,5
Flash point	°C	215

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

Version 2 / 2024-03-11